



BEARING USA CORP.



130 mm x 180 mm x 24 mm 634 Ceramic Bearing

Bearing No. 6926

6926 Bearing 2D drawings and 3D CAD models

Size	130x180x24 mm
Bore Diameter	130 mm
Outer Diameter	180 mm
Width	24 mm
d	130 mm
D	180 mm
B	24 mm
C	24 mm
r min.	1,5 mm
da min.	138 mm
da max	144 mm
Da max.	172 mm
ra max.	1,5 mm
Weight	1,57 Kg
Basic dynamic load rating (C)	65 kN
Basic static load rating (C0)	67,5 kN
(Grease) Lubrication Speed	3 400 r/min
(Oil) Lubrication Speed	4 000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	1.5
EAN	0029176066825
Product Group	B00308



BEARING USA CORP.

Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	130MM Bore; 180MM Outside Diameter; 24MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features; C0-Medium Internal Clearance; Steel Cage
Other Features	Deep Groove
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.nskamericas.com
Weight / LBS	3.4619
Bore	5.118 Inch 130 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.945 Inch 24 Millimeter
Outside Diameter	7.087 Inch 180 Millimeter
SRI	7.8
hidYobi	6926
LangID	1



BEARING USA CORP.

D_	180
SREX	0.03
B_	24
da min	138
hidTable	ecat_NSRDGB
Oil rpm	4000
SRE	7.8
mass	1.57
GRS rpm	3400
ra	1.5
SRIX	0.03
D_a	172
SRIN	-0.03
C0	67.5
fo	16.5
SREN	-0.03
DE_	170.081
Prod_Type3	DGBB_SR_OT
DA_	15.081
bomp	0
Z_	18
yobi	6926
C_conv	65000
ALPHA_	0
SDM_	155
r	1.5
KBRG	6101
SBRG	19
DI_	139.919